


## Cataclean Cleaning Agent for catalytic converters



HEALTH		1
FLAMMABILITY		3
PHYSICAL		0
PPE		B



Printed: 12/19/2013  
Revision: 1/3/2017  
Supersedes Revision: 08/31/2004  
Date Created: 08/31/2004

## 1. Product and Company Identification

**Product Code:** CATACLEAN

**Product Name:** Cataclean Cleaning Agent for catalytic converters

**Trade Name:** Cataclean Cleaner blend

**Manufacturer Information**

**Company Name:** Fas-Pak, Inc.  
411 Fairfield Avenue  
Michigan City, IN 46360

**Phone Number:** (219)874-7990

**Fax Number:** (219)874-7991

**Information:** EHS Manager (219)874-7990

**Web site address:** www.fas-pak.com

**Preparer Name:** RTW

**Chemical Family:** Petroleum Hydrocarbon Solvent

**CAS Number:** 1330-20-7

**RTECS #:** ZE2100000

**Synonyms**  
Xylol; Mixed Xylenes

## 2. Hazards Identification

GHS Classification	Placard	Key word	GHS hazard phrase
Flammable Liquids, Category 2	Flame	Danger	Highly flammable liquid and vapor
Acute Toxicity: Inhalation, Category 4	Exclamation point	Warning	Harmful if inhaled
Acute Toxicity: Skin, Category 4	Exclamation point	Warning	Harmful in contact with skin
Skin Corrosion/Irritation, Category 2	Exclamation point	Warning	Causes skin irritation
Serious Eye Damage/Eye Irritation, Category 1	Corrosive	Danger	Causes serious eye damage
Target Organ Systemic Toxicity (single exposure), Category 3	Exclamation point	Warning	May cause respiratory irritation, or may cause drowsiness and dizziness
Aspiration Toxicity, Category 1	Health hazard	Danger	May be fatal if swallowed and enters airways.

### GHS Hazard Phrases

H225: Highly flammable liquid and vapor.  
H332: Harmful if inhaled.  
H312: Harmful in contact with skin.  
H315: Causes skin irritation.  
H318: Causes serious eye damage.  
H336: May cause drowsiness or dizziness.  
H304: May be fatal if swallowed and enters airways.  
H303: May be harmful if swallowed.

## Cataclean Cleaning Agent for catalytic converters

Printed: 12/19/2013

Revision: 1/3/2017

Supersedes Revision: 08/31/2004

**GHS Precaution Phrases**

- P233: Keep container tightly closed.
- P210: Keep away from {heat/sparks/open flames/hot surfaces}. - No smoking.
- P280: Wear {protective gloves/protective clothing/eye protection/face protection}.
- P240: Ground/bond container and receiving equipment.
- P241: Use explosion-proof electrical/ventilating/lighting/{.../} equipment.
- P243: Take precautionary measures against static discharge.
- P242: Use only non-sparking tools.
- P271: Use only outdoors or in a well-ventilated area.
- P261: Avoid breathing {dust/fume/gas/mist/vapours/spray}.
- P264: Wash {hands} thoroughly after handling.
- P362+364: Take off contaminated clothing and wash it before reuse.

**GHS Response Phrases**

- P370+378: In case of fire, use {...} to extinguish.
- P303+361+353: IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P312: Call a {POISON CENTER/doctor/...} if you feel unwell.
- P302+352: IF ON SKIN: Wash with plenty of soap and water.
- P322: Specific measures {see ... on this label}.
- P363: Wash contaminated clothing before reuse.
- P321: Specific treatment {see ... on this label}.
- P332+313: If skin irritation occurs, get medical advice/attention.
- P362: Take off contaminated clothing.
- P305+351+338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P310: Immediately call a {POISON CENTER/doctor/...}.
- P309+311: Call a POISON CENTER or doctor/physician if exposed or you feel unwell.
- P301+310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
- P331: Do NOT induce vomiting.

**GHS Storage and Disposal Phrases**

- P403+235: Store in cool/well-ventilated place.
- P501: Dispose of contents/container to {...}.
- P405: Store locked up.
- P403+233: Store container tightly closed in well-ventilated place - if product is as volatile as to generate hazardous atmosphere.

**Potential Health Effects (Acute and Chronic)**

EYES: May cause mild irritation.

SKIN: Can cause skin irritation. Prolonged or repeated contact may dry the skin.

SWALLOWING: Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts (1/8 of a cup or more), may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung injury and chemical pneumonia, including possible death.

INHALATION: breathing of vapor or mist is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts and repeated exposure over time may be harmful. Symptoms usually occur at air concentrations higher than the recommended exposure limits.

## Cataclean Cleaning Agent for catalytic converters

Printed: 12/19/2013

Revision: 1/3/2017

Supersedes Revision: 08/31/2004

**TARGET ORGAN EFFECTS:** Over exposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals: testis damage, kidney damage, liver damage, and effects on hearing. Overexposure to this material (or its components) has been suggested as a cause of the following effects in humans: Central Nervous System effects.

**DEVELOPMENTAL INFORMATION:** This material, or a component, may be harmful to the human fetus based on positive test results with laboratory animals.

**LD 50 / LC 50**

Causes eye irritation.

**Medical Conditions Generally Aggravated By Exposure**

Skin, lungs (for example, asthma-like conditions), liver, kidney, central nervous system, male reproductive system, and auditory system. Individuals with preexisting heart disorders may be more susceptible to arrhythmias (irregular heartbeats) if exposed to high concentrations of this material.

### 3. Composition/Information on Ingredients

Hazardous Components (Chemical Name)	CAS #	Concentration
1. Hydrotreated light distillate (petroleum)	64742-47-8	5.0 -10.0 %
2. Xylene (mixed isomers)	1330-20-7	30.0 -60.0 %
3. 1-Propanol	71-23-8	10.0 -30.0 %
4. Acetone	67-64-1	10.0 -30.0 %

### 4. First Aid Measures

**Emergency and First Aid Procedures**

Take proper precautions to ensure your own health and safety before attempting rescue or providing first aid.

**EYES:** Check for and remove contact lenses.

If irritation or redness develops, flush eyes with cool, clean, low pressure water for at least 15 minutes.

Hold eyelids apart to ensure complete irrigation of the eye and eyelid tissue.

Do not use eye ointment.

Seek medical attention immediately.

**SKIN:** Remove contaminated shoes and clothing. Flush exposed areas with large amounts of water.

If skin is damaged, apply a clean dressing and seek immediate medical attention. do not use ointments.

If skin is not visibly damaged (blistering, redness), clean the affected area thoroughly with mild soap and water.

Seek medical attention if tissue appears damaged or if pain or irritation persists.

**SWALLOWING:** Do not induce vomiting. If spontaneous vomiting is about to occur, place victim's head below knees.

If victim is drowsy or unconscious, place on left side with head down.

Never give anything by mouth to a person who is not fully conscious.

Do not leave victim unattended.

Seek medical attention immediately.

**INHALATION:** Immediately move victim to fresh air.

If victim is not breathing, immediately begin CPR.

If breathing is difficult, 100% humidified oxygen should be administered by a qualified individual.

Seek medical attention immediately.

## Cataclean Cleaning Agent for catalytic converters

Printed: 12/19/2013

Revision: 1/3/2017

Supersedes Revision: 08/31/2004

**In Case of Inhalation**

Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Get immediate medical attention.

**In Case of Skin Contact**

Rinse cautiously with water for several minutes.

**In Case of Eye Contact**

Flush eye with water for 15 minutes. Get medical attention.

**In Case of Ingestion**

IF SWALLOWED: Do not induce vomiting. Give milk or water. Get immediate medical attention. Careful evacuation of stomach by medical personnel imperative.

**Note to Physician**

Inhalation overexposure can produce toxic effects. Monitor for respiratory distress. If cough or breathing difficulty develops, evaluate for upper respiratory inflammation, bronchitis, and pneumonitis. Administer supplemental oxygen with assisted ventilation, as required.

This material sensitizes the heart to the effects of sympathomimetic amines. Epinephrine and other Sympatomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material. Administration of sympathomimetic drugs should be avoided.

INGESTION: This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity when deciding whether to induce vomiting. Also, signs of chemical pneumonia may be delayed up to 48 hours, presenting only after moderate physical exertion. Induction of emesis is not recommended. Consider activated charcoal and/ or gastric lavage. If patient is outbound, protect the airway by cuffed endotracheal intubation or by placement of the body in a Trendelenburg and left lateral decubitus position.

**Signs and Symptoms of Exposure**

EYES: stinging, tearing, redness and blurred vision.

SKIN: redness, burning, drying and cracking of skin, chemical burns, blistering, and other skin damage.

Signs and symptoms of exposure through skin absorption, swallowing, or inhalation may include: redness of the face and neck, mouth and throat irritation, (soreness, dry or scratchy feeling, cough), stomach or intestinal upset (nausea, vomiting, diarrhea), irritation of the nose, throat, and airways, tight feeling in the chest, central nervous system excitation (giddiness, liveliness, light headed feeling), followed by central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness) and other central nervous system effects; effects on memory; respiratory depression (slowing of breathing rate); shortness of breath, loss of coordination, confusion, irregular heartbeat, narcosis (dazed or sluggish feeling), coma.

**5. Fire Fighting Measures**

<b>Flammability Classification:</b>	Flammable Liquid
<b>Flash Pt:</b>	80.00 F (26.7 C) Method Used: TAG Closed Cup
<b>Explosive Limits:</b>	LEL: 1.0 UEL: 6.6
<b>Autoignition Pt:</b>	980.00 F (526.7 C)

**Fire Fighting Instructions**

Wear a SCBA with a full facepiece operated in positive pressure demand mode with appropriate turn out gear and chemical resistant personal protective equipment. Refer to the PPE section (#8) of this MSDS.

**Flammable Properties and Hazards**

VAPORS ARE HEAVIER THAN AIR AND MAY TRAVEL ALONG THE GROUND OR MAY BE MOVED BY VENTILATION AND IGNITED BY PILOT LIGHTS, OTHER FLAMES, SPARKS, HEATERS, SMOKING, ELECTRIC MOTORS, STATIC DISCHARGE, OR OTHER IGNITION SOURCES AT

## Cataclean Cleaning Agent for catalytic converters

Printed: 12/19/2013

Revision: 1/3/2017

Supersedes Revision: 08/31/2004

LOCATIONS DISTANT FROM THE MATERIAL HANDLING POINT.

NEVER USE WELDING OR CUTTING TORCH ON OR NEAR DRUM (EVEN EMPTY) BECAUSE PRODUCT, VAPORS, OR RESIDUE CAN IGNITE EXPLOSIVELY.

**Hazardous Combustion Products**

Carbon dioxide, carbon monoxide, and various hydrocarbons.

**Suitable Extinguishing Media**

Regular foam, carbon dioxide, or dry chemical.

**Unsuitable Extinguishing Media**

No data available.

## 6. Accidental Release Measures

**Steps To Be Taken In Case Material Is Released Or Spilled**

SMALL SPILL: Absorb liquid with vermiculite, Oil-Dri, or sand.

LARGE SPILL: Eliminate all ignition sources (flares, flames, pilot lights, electrical sparks).

Persons not wearing respirators and other required protective equipment should be excluded from the area of spill until clean up has been completed.

Turn off all valves and pumps to stop spill at source.

Prevent from entering drains, sewers, streams, or other bodies of water. Prevent from spreading by diking or berming.

If runoff occurs, notify the EHS Manager immediately.

Pump or vacuum transfer (make sure grounded!) spilled product to clean, labelled containers for recovery.

Absorb unrecoverable product with inert material such as Oil-dri. Transfer contaminated absorbent and other materials to SPILLS OF 100 LBS. (or 725 Gallons) OR MORE MUST BE REPORTED TO LOCAL, STATE, AND FEDERAL AGENCIES UNDER CERCLA.

## 7. Handling and Storage

**Hazard Label Information:**

Do not reuse this container. Do not get on skin and clothing. Keep away from heat and flame. Keep away from sources of ignition.

**Precautions To Be Taken in Handling**

Containers of this material may be hazardous when emptied. Since emptied containers retain product residue (vapor/ liquid/ and/or solid), all hazard precautions given in the data sheet must be observed.

All 5-gallon pails and larger metal containers, including tank cars and tank trucks, should be grounded and/ or bonded when material is transferred. Hydrocarbon solvents are non-conductors of electricity and as such can become electrostatically charged during mixing, filtering, or pumping at high flow rates. If this charge reaches a sufficiently high level, sparks can form that may ignite the vapors of flammable liquids.

WARNING: Sudden release of hot organic chemical vapors or mists from process equipment operating at elevated temperature and/ or pressure, or sudden ingress of air into vacuum equipment, may result in ignitions without the presence of obvious ignition sources. Published "Autoignition" temperature values cannot be treated as safe operating temperatures in chemical processes without analysis of the actual process conditions. Any use of this product in elevated temperature processes should be thoroughly evaluated to establish and maintain safe operating conditions.

**Precautions To Be Taken in Storing**

Keep away from oxidizers, heat and flames. May attack some plastics, rubber and coating. Keep in tightly closed containers in a cool, dry, ventilated storage area. Ground container and transfer equipment to eliminate static sparks. This product should be stored away from any incompatible materials (see Section 10).

## Cataclean Cleaning Agent for catalytic converters

Printed: 12/19/2013

Revision: 1/3/2017

Supersedes Revision: 08/31/2004

## 8. Exposure Controls/Personal Protection

Hazardous Components (Chemical Name)	CAS #	OSHA PEL	ACGIH TWA	Other Limits
1. Hydrotreated light distillate (petroleum)	64742-47-8	No data.	TLV: 200 mg/m3	No data.
2. Xylene (mixed isomers)	1330-20-7	PEL: 100 ppm	TLV: 100 ppm	No data.
3. 1-Propanol	71-23-8	PEL: 200 ppm	TLV: 200 ppm STEL: (250 ppm)	No data.
4. Acetone	67-64-1	PEL: 1000 ppm	TLV: 500 ppm STEL: 750 ppm	No data.

**Protective Equipment Summary - Hazard Label Information:**

Chemical resistant apron    Chemical resistant boots    Clothes to prevent skin contact    Eye wash station in work area  
NIOSH/MSHA organic vapor respirator    Safety shower in work area

**Respiratory Equipment (Specify Type)**

For Blending or Drum Filling, Respirator with Organic vapor cartridge is required.

**Eye Protection**

Chemical splash goggles are advised; however, OSHA regulations also permit other type of safety glasses, depending on the task at hand. If you are working in close proximity, such as filling drums or blending, wear splash goggles.

**Protective Gloves**

Chemical resistant gloves.

**Other Protective Clothing**

To prevent repeated or prolonged skin contact, wear impervious clothing and boots. REQUIRED AT FAS-PAK FOR ALL PERSONS DOING BLENDING/ FILLING OPERATIONS WITH THIS MATERIAL.

**Engineering Controls (Ventilation etc.)**

EXHAUST AND VENTILATION SHOULD KEEP LEVELS AT OR BELOW SAFE Threshold Limit Values ESTABLISHED BY OSHA.

**Work/Hygienic/Maintenance Practices**

Do no eat, drink, or smoke on the job.

Wash hands thoroughly before breaks and before going home.

## 9. Physical and Chemical Properties

<b>Physical States:</b>	[ ] Gas    [X] Liquid    [ ] Solid
<b>Melting Point:</b>	-54.00 F (-47.8 C)
<b>Boiling Point:</b>	~ 210.00 F (98.9 C) - 55.00 C (131.0 F)
<b>Autoignition Pt:</b>	980.00 F (526.7 C)
<b>Flash Pt:</b>	80.00 F (26.7 C)    Method Used: TAG Closed Cup
<b>Explosive Limits:</b>	LEL: 1.0                      UEL: 6.6
<b>Specific Gravity (Water = 1):</b>	~ 0.815 - 0.835    at 60.0 F (15.6 C)
<b>Density:</b>	7.25 LB/GA    at 60.0 F (15.6 C)
<b>Vapor Pressure (vs. Air or mm Hg):</b>	~ 9.00 MM_HG    at 68.0 F (20.0 C)
<b>Vapor Density (vs. Air = 1):</b>	~ 3.66
<b>Evaporation Rate:</b>	0.66
<b>Solubility in Water:</b>	~ 55 %
<b>Percent Volatile:</b>	100.0 % by weight.
<b>VOC / Volume:</b>	870.0000 G/L
<b>Viscosity:</b>	0.80 CPS

## Cataclean Cleaning Agent for catalytic converters

Printed: 12/19/2013

Revision: 1/3/2017

Supersedes Revision: 08/31/2004

**Heat Value:** 18445 BTU  
**Octanol/Water Partition Coefficient:** 3.120-3.200  
**Formula:** C6H4(CH3)2  
**Molecular Weight:** 106.16  
**pH:** NA

**Appearance and Odor**

Clear light blue liquid with characteristic alcohol like and sweet aromatic odor.

**10. Stability and Reactivity**

**Stability:** Unstable [ ] Stable [ X ]

**Conditions To Avoid - Instability**

All sources of heat, flame, and potential ignition sources.

**Incompatibility - Materials To Avoid**

Strong oxidizing conditions and agents, strong acids, & alkalis such as liquid chlorine, hydrogen peroxide, and oxygen.

**Hazardous Decomposition Or Byproducts**

Carbon dioxide, carbon monoxide, and various hydrocarbons.

**Possibility of Hazardous Reactions:** Will occur [ ] Will not occur [ X ]

**Conditions To Avoid - Hazardous Reactions**

No data available.

**11. Toxicological Information****Toxicological Information**

See Section #3, Hazards.

**Carcinogenicity/Other Information**

IARC has classified Ethylbenzene as a possible human carcinogen.

Hazardous Components (Chemical Name)	CAS #	NTP	IARC	ACGIH	OSHA
1. Hydrotreated light distillate (petroleum)	64742-47-8	n.a.	n.a.	A4	n.a.
2. Xylene (mixed isomers)	1330-20-7	n.a.	3	A4	n.a.
3. 1-Propanol	71-23-8	n.a.	n.a.	n.a.	n.a.
4. Acetone	67-64-1	n.a.	n.a.	A4	n.a.

**Carcinogenicity:** NTP? No IARC Monographs? Yes OSHA Regulated? No

**12. Ecological Information****General Ecological Information**

Xylene and Ethylebenzene have a low order of toxicity and biopersistance due to the high volatility of both compounds. Soil studies indicate 98% evaporation after 6 hours.

**13. Disposal Considerations****Waste Disposal Method**

DISPOSE OF AS A SOLVENT WASTE. MUST BE RECYCLED.

**RCRA Waste ID Code:** U239

**14. Transport Information****LAND TRANSPORT (US DOT)**

**DOT Hazard Class:** 3  
**DOT Hazard Label:** FLAMMABLE LIQUID  
**UN/NA Number:** UN1993

## Cataclean Cleaning Agent for catalytic converters

Printed: 12/19/2013

Revision: 1/3/2017

Supersedes Revision: 08/31/2004

**Packing Group:** III  
**LAND TRANSPORT (Canadian TDG)**  
**TDG Shipping Name** Flammable liquids, n.o.s.

**LAND TRANSPORT (European ADR/RID)**  
**ADR/RID Shipping Name** Flammable liquids, n.o.s.

**AIR TRANSPORT (ICAO/IATA)**  
**ICAO/IATA Shipping Name** Flammable liquids, n.o.s.  
**UN Number:** 1993  
**Hazard Class:** 3 - FLAMMABLE LIQUID  
**Packing Group:** III

**MARINE TRANSPORT (IMDG/IMO)**  
**IMDG/IMO Shipping Name** Flammable liquids, n.o.s.  
**UN Number:** 1993  
**Hazard Class:** 3 - FLAMMABLE LIQUID  
**Packing Group:** III  
**Marine Pollutant:** Yes

**Additional Transport Information**

THE TRANSPORT INFORMATION MAY VARY WITH THE CONTAINER AND MODE OF SHIPMENT.

**15. Regulatory Information****US EPA SARA Title III**

Hazardous Components (Chemical Name)	CAS #	Sec.302 (EHS)	Sec.304 RQ	Sec.313 (TRI)	Sec.110
1. Hydrotreated light distillate (petroleum)	64742-47-8	No	No	No	No
2. Xylene (mixed isomers)	1330-20-7	No	Yes 100 LB	Yes	Yes
3. 1-Propanol	71-23-8	No	No	No	No
4. Acetone	67-64-1	No	Yes 5000 LB	No	Yes

**US EPA CAA, CWA, TSCA**

Hazardous Components (Chemical Name)	CAS #	EPA CAA	EPA CWA NPDES	EPA TSCA	CA PROP 65
1. Hydrotreated light distillate (petroleum)	64742-47-8	No	No	Inventory	No
2. Xylene (mixed isomers)	1330-20-7	HAP	Yes	Inventory	No
3. 1-Propanol	71-23-8	No	No	Inventory	No
4. Acetone	67-64-1	No	No	Inventory, 4 Test	No

**SARA (Superfund Amendments and Reauthorization Act of 1986) Lists:**

**Sec.302:** EPA SARA Title III Section 302 Extremely Hazardous Chemical with TPQ. \* indicates 10000 LB TPQ if not volatile.

**Sec.304:** EPA SARA Title III Section 304: CERCLA Reportable + Sec.302 with Reportable Quantity. \*\* indicates statutory RQ.

**Sec.313:** EPA SARA Title III Section 313 Toxic Release Inventory. Note: -Cat indicates a member of a chemical category.

**Sec.110:** EPA SARA 110 Superfund Site Priority Contaminant List

**TSCA (Toxic Substances Control Act) Lists:**

**Inventory:** Chemical Listed in the TSCA Inventory.

**5A(2):** Chemical Subject to Significant New Rules (SNURS)



## Cataclean Cleaning Agent for catalytic converters

Printed: 12/19/2013

Revision: 1/3/2017

Supersedes Revision: 08/31/2004

<b>6A:</b>	Commercial Chemical Control Rules
<b>8A:</b>	Toxic Substances Subject To Information Rules on Production
<b>8A CAIR:</b>	Comprehensive Assessment Information Rules - (CAIR)
<b>8A PAIR:</b>	Preliminary Assessment Information Rules - (PAIR)
<b>8C:</b>	Records of Allegations of Significant Adverse Reactions
<b>8D:</b>	Health and Safety Data Reporting Rules
<b>8D TERM:</b>	Health and Safety Data Reporting Rule Terminations
<b>12(b):</b>	Notice of Export

**Other Important Lists:**

<b>CWA NPDES:</b>	EPA Clean Water Act NPDES Permit Chemical
<b>CAA HAP:</b>	EPA Clean Air Act Hazardous Air Pollutant
<b>CAA ODC:</b>	EPA Clean Air Act Ozone Depleting Chemical (1=CFC, 2=HCFC)
<b>CA PROP 65:</b>	California Proposition 65

**International Regulatory Lists:****EPA Hazard Categories:**

This material meets the EPA 'Hazard Categories' defined for SARA Title III Sections 311/312 as indicated:

- Yes [ ] No Acute (immediate) Health Hazard  
 Yes [ ] No Chronic (delayed) Health Hazard  
 Yes [ ] No Fire Hazard  
 Yes [ ] No Sudden Release of Pressure Hazard  
 Yes  No Reactive Hazard

## 16. Other Information

**Company Policy or Disclaimer**

NOTICE: The information presented herein is based on data considered to be accurate as of the date of this Material Safety Data Sheet. However, an MSDS may not be used as a commercial specification sheet of manufacturer or seller, and no warranty or representation, expressed or implied, is made as to the accuracy or comprehensiveness of the foregoing data and safety information, nor is any authorization given or implied to practice any patented invention without a license. In addition, no responsibility can be assumed by vendor for any damage or injury resulting from abnormal use, from any failure to adhere to recommended practices, or from any hazards inherent in the nature of the material.

**Revision Date:** 1/3/2017