



Product Information 02.35.39

16-04-2014

SP Matic 2092

Description

SP Matic 2092 is a premium, synthetic Long Life ATF, specially designed for electronically-controlled transmissions and the friction clutches used inside it. As a result, SP Matic 2092 enables very comfortable and superbly quiet gear-changing.

SP Matic 2092 features the following properties:

- Very high resistance to oxidation and therefore perfect for life-time application
- Outstanding lubrication properties
- Excellent protection against corrosion and foaming
- Excellent low-temperature properties
- Fully compatible with seal agents used by Mercedes

Application

SP Matic 2092 has been specially developed for the new generation of 7-speed 7G-Tronic transmissions by Mercedes-Benz for which the MB 236.14 specification is required. The product can also be used in automatic transmissions produced by Mercedes-Benz for which the older MB 236.12 specification is required. SP Matic 2092 is also suitable for use in the 6HP series of automatic transmissions from ZF.

Specifications

MB 236.14 Ssang Yong (MB-Automatic transmissions)

Typicals

Colour	ROOD
Density at 15 °C, kg/l	0,850
Viscosity -35 °C, mPa.s	4260
Viscosity -40 °C, mPa.s	8500
Viscosity 40 °C, mm ² /s	29,60
Viscosity 100 °C, mm ² /s	6,50
Viscosity Index	185

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.



Flash Point COC, °C	200
Pour Point, °C	-51

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.