

Product Details

FS	Full Synthetic
Application	Gasoline Normally Aspirated

Product Specifications

Flash Point C	204
Flash point F	399
Pour Point C	-42
Pour Point F	-43
Specific Gravity @ 15.6	0.849
Viscosity @ 100 C, CST	8.50
Viscosity @ 40 C, CST	49.00

Product Packaging

Pail	20 Liter
Drum	205 Liter

Product Notes

- Should only be used where a 5W-20 engine lubricant is recommended by a vehicle manufacturer
- Always consult vehicle owner's manual for the correct engine lubricant specification and drain interval period.

Industry Standards

API	SN	Gas
ILSAC	GF-5	Gas

Performance Level

Acura (1)	
Buick	GM6094A
Cadillac	GM6094A
Chevrolet	GM6094A
Chrysler	MS-6395
Dodge	MS-6395
Ford	WSS-M2C153-H
Ford	WSS-M2C925-A
Ford	WSS-M2C930-A
Ford	WSS-M2C945-A
General Motors	GM6094A
GMC	GM6094A
Honda (1)	
Jaguar	WSS-M2C925-A
Jeep	MS-6395
Land Rover	WSS-M2C925-A
Lexus	
Lincoln	WSS-M2C153-H
Lincoln	WSS-M2C925-A
Lincoln	WSS-M2C930-A
Lincoln	WSS-M2C945-A
Mazda	
Mercury	WSS-M2C153-H
Mercury	WSS-M2C925-A
Mercury	WSS-M2C930-A
Mercury	WSS-M2C945-A
Mitsubishi	
Saturn	GM6094A
Scion	
Toyota	

(1) Excluding: Acura/Honda HTO-06

THE RECOMMENDATIONS OR SUGGESTIONS MADE IN THIS SHEET ARE MADE WITHOUT GUARANTEE OR REPRESENTATION AS TO RESULTS. THE CONTENT OF THIS SHEET IS CORRECT TO THE BEST OF OUR KNOWLEDGE. WE ADVISE THE READER TO CAREFULLY EVALUATE THE PRODUCT CHOICE FOR CRITICAL APPLICATIONS TOGETHER WITH THE SUPPLIER. WE DO NOT ACCEPT RESPONSIBILITY FOR DAMAGE AS A CONSEQUENCE OF INCOMPLETENESS OR, NEGLIGENCE AND INACCURACIES IN THIS INFORMATION SHEET. ALL TERMS OF SALE OF THE SUPPLIER CAN BE APPLIED HERE. **1505B/1503.**