



MAINTENANCE CHECK SHEET

2010MY - Onwards XF 5.0L

DEALER CODE / NAME	VIN									
	1	2	3	4	5	6	7	8	9	10
⊙ TIME (Years)	15	30	45	60	75	90	105	120	135	150
⊙ MILES (Thousands)	24	48	72	96	120	144	168	192	216	240
⊙ KM (Thousands)	⊙'Nominal' distance values for normal driving. See Passport to Service for additional information.									
1. VEHICLE INTERIOR										
Check operation of electronic parking brake	■	■	■	■	■	■	■	■	■	■
Check operation of all lights, warning indicators, and horn	■	■	■	■	■	■	■	■	■	■
Check operation of windshield wiper / washer systems	■	■	■	■	■	■	■	■	■	■
Replace climate controlled seat cushion motor filters (if fitted)		■		■		■		■		■
2. VEHICLE EXTERIOR										
Inspect windshield wiper blades and rubber inserts	■	■	■	■	■	■	■	■	■	■
Check tire pressure, condition and tread depth - record on page 2	■	■	■	■	■	■	■	■	■	■
3. LUGGAGE COMPARTMENT										
Check spare tire pressure, condition and tread depth - record on page 2	■	■	■	■	■	■	■	■	■	■
Check and top-up battery electrolyte level		■		■		■		■		■
4. ENGINE COMPARTMENT										
Check and top-up brake, PAS and windshield washer fluid	■	■	■	■	■	■	■	■	■	■
Check coolant level and freeze protection level	■	■	■	■	■	■	■	■	■	■
Inspect accessory drive and (if equipped) supercharger belt	■	■	■	■	■	■	■	■	■	■
Replace engine oil and oil filter	■	■	■	■	■	■	■	■	■	■
Replace pollen filter		■		■		■		■		■
Replace air cleaner elements - supercharged				■			■			■
Replace air cleaner elements - naturally aspirated					■					■
Replace brake fluid	Every three years regardless of mileage									
Replace spark plugs	Every 105,000 mi / 168,000 km									
Replace supercharger drive belt (if equipped)	Every 105,000 mi / 168,000 km									
Replace engine coolant	10 years or 150,000 mi / 240,000 km									
Replace accessory drive belt	@ 150,000 mi / 240,000 km									
5. UNDER VEHICLE										
Inspect for brake pad wear, caliper leaks and disc condition	■	■	■	■	■	■	■	■	■	■
Check tire pressures, condition and tread depth	■	■	■	■	■	■	■	■	■	■
Inspect for under vehicle fluid leaks	■	■	■	■	■	■	■	■	■	■
Inspect brake lines and hoses, fuel lines, PAS hoses and unions for correct routing and damage	■	■	■	■	■	■	■	■	■	■
Replace fuel filter	10 years or 150,000 mi / 240,000 km									
6. REMEDIAL WORK / SERVICE CAMPAIGN NEEDED										
If fault lamps illuminated use IDS for further diagnosis / repair	■	■	■	■	■	■	■	■	■	■
Check VIN in DDW for any open Service Campaigns										



MAINTENANCE CHECK SHEET

2010MY - Onwards XF 5.0L

⊙ TIME (Years)	1	2	3	4	5	6	7	8	9	10
⊙ MILES (Thousands)	15	30	45	60	75	90	105	120	135	150
⊙ KM (Thousands)	24	48	72	96	120	144	168	192	216	240
7. ROAD TEST										
Perform comprehensive road test and verify the following:	■	■	■	■	■	■	■	■	■	■
• Correct operation of Jaguar Drive™ Selector and transmission interlock										
• Correct operation of fault lamps and instruments										
• Condition and operation of seatbelts										
• Operation of steering column and seat adjustment mechanisms										
• Starter motor operates normally and engine starts easily										
• Steering self-centers from left and right-hand turns										
• Vehicle does not pull or wander to one side										
• Brakes operate smoothly without judder, noise, or pull to one side										
• Transmission shifts up and down smoothly; Jaguar Sequential Shift™ operation										
• Cruise control operation										
• Climate control operation										
• Inspect for undue vehicle noises										
8. FINAL										
• Reset service interval announcement indicator										
• Reset engine oil level indicator										
• Endorse service record										
• Affix next service reminder sticker										
• Report any unusual features of vehicle condition and additional / remedial work required										

NOTE: Some service items do not need to be carried out at every service. All required steps in a specific service are identified in the column headed by mileage / months with a '■'.

- Should the vehicle have a high proportion of short journeys or operate in severe conditions, Jaguar North America recommends that the maintenance procedures be performed at intervals not to exceed six (6) months.

TIRE TREAD DEPTH (including spare)	L / F:	R / F:
	L / R:	R / R:
	SPARE:	

TECHNICIAN COMMENTS & REMEDIAL ACTION REQUIRED

TECHNICIAN SIGNATURE _____

DATE _____