

**Services should be performed within 2,500 miles of the specified mileage. For example, the 10,000 mile service should be performed between 7,500 and 12,500 miles.**

**Should the vehicle have a high proportion of short journeys or operate in severe conditions, Jaguar Cars recommends that the maintenance procedures scheduled at 10,000-mile intervals be performed at intervals not to exceed 6 months.**

Service (miles x 1,000)	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150
Check / top up brake fluid level	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Check / top up coolant level	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Check / top up power assisted steering fluid level	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Check / top up windshield washer fluid level	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Check / top up battery electrolyte level	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Check drive belt tension wear indicator(s); replace belt(s) if necessary or as specified	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Check suspension dampers for fluid or air leaks; X1 models only	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Visually check under hood and under body for any fluid leaks	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Replace air filter element: all models except X-TYPE	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Replace air filter element: X-TYPE models only	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Replace fuel filter: all models except X-TYPE	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Replace fuel filter: X-TYPE models only	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
Replace brake fluid	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
<b>Every 2 years regardless of mileage</b>															

Service (miles x 1,000)	10	20	30	40	50	60	70	80	90	100	110	120	130	140	150
Replace engine coolant: all models except XK															
Replace engine coolant: XK models only															
Replace spark plugs	●														
Replace accessory drive belt: all models except XK		●													
Replace accessory drive belt: XK models only			●												
Replace rear drive belt: X-TYPE models only				●											
Replace Supercharger drive belt: XJ and S-TYPE models					●										
Replace engine oil, oil filter and sump washer						●									
Inspect brake pads for wear (check rotor condition on pad change)							●								
Replace pollen filter: all models except S-TYPE								●							
Replace pollen filter: S-TYPE models only									●						
Inspect windshield wiper blades for wear or deterioration										●					
Apply Jaguar Screen Clean paste to the windshield exterior											●				
Check tire pressure, tread depth and general condition; check for signs of uneven wear; check that tires are correct size and type (check should include spare tire)												●			
Conduct road test; verify parking brake operation													●		
Replace airbag SRS														Required every 15 years	