1. IDENTIFICATION OF THE S	UBS	STANCE/PREPARATION AND COMPANY/UNDERTAKING
Material Name Uses Product Code	:	Shell ATF M-1375.4 Transmission oil. 901L3470
Manufacturer/Supplier	:	Shell UK Oil Products Limited Shell Centre London SE1 7NA United Kingdom
Telephone Email Contact for MSDS	:	(+44) 08708500939 If you have any enquiries about the content of this MSDS please email lubricantSDS@shell.com
Emergency Telephone Number	:	+44-(0) 151-350-4595
2. HAZARDS IDENTIFICATION		
EC Classification	:	Not classified as dangerous under EC criteria.
Health Hazards	:	Not expected to be a health hazard when used under normal conditions. Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis. Used oil may contain harmful impurities.
Signs and Symptoms	:	Oil acne/folliculitis signs and symptoms may include formation of black pustules and spots on the skin of exposed areas. Ingestion may result in nausea, vomiting and/or diarrhoea.
Safety Hazards Environmental Hazards	:	Not classified as flammable but will burn. Not classified as dangerous for the environment.
3. COMPOSITION/INFORMATI	ON	ON INGREDIENTS
Preparation Description	:	Highly refined mineral oil, severely hydrotreated slack wax and additives. Contains polyolefins.
Hazardous Components		

Chemical Name	CAS No.	EINECS	REACH Registration No.	Symbol(s)	R-phrase(s)	Conc.
Calcium sulphonate				Xi	R43	0.10 - 0.90%
Ethoxylated amine	25307-17-9	246-807-3		C, Xn, N	R22; R34; R43; R50	0.10 - 0.90%

Additional Information : The highly refined mineral oil contains <3% (w/w) DMSOextract, according to IP346. Refer to chapter 16 for full text of EC R-phrases.

4. FIRST AID MEASURES

General Information	: Not expected to be a health hazard when used under normal conditions.
Inhalation	 No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
Skin Contact	: Remove contaminated clothing. Flush exposed area with water and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.
Eye Contact	: Flush eye with copious quantities of water. If persistent irritation occurs, obtain medical attention.
Ingestion	 In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.
Advice to Physician	: Treat symptomatically.

5. FIRE FIGHTING MEASURES

Clear fire area of all non-emergency personnel.

Specific Hazards	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide. Unidentified organic and inorgar compounds.	nic
Suitable Extinguishing Media	Foam, water spray or fog. Dry chemical powder, carbon dioxide, sand or earth may be used for small fires only.	
Unsuitable Extinguishing Media	Do not use water in a jet.	
Protective Equipment for Firefighters	Proper protective equipment including breathing apparatus must be worn when approaching a fire in a confined space.	

6. ACCIDENTAL RELEASE MEASURES

Avoid contact with spilled or released material. For guidance on selection of personal protective equipment see Chapter 8 of this Material Safety Data Sheet. See Chapter 13 for information on disposal. Observe the relevant local and international regulations.

Protective measures Clean Up Methods Additional Advice	 Avoid contact with skin and eyes. Use appropriate containment to avoid environmental contamination. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers. Slippery when spilt. Avoid accidents, clean up immediately. Prevent from spreading by making a barrier with sand, earth or other containment material. Reclaim liquid directly or in an absorbent. Soak up residue with an absorbent such as clay, sand or other suitable material and dispose of properly. Local authorities should be advised if significant spillages cannot be contained.
7. HANDLING AND STORAGE	
General Precautions	: Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Properly dispose of any contaminated rags or cleaning materials in order to prevent fires. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
Handling	: Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used.
Storage	 Keep container tightly closed and in a cool, well-ventilated place. Use properly labelled and closeable containers. Storage Temperature: 0 - 50°C / 32 - 122°F The storage of this product may be subject to the Control of Pollution (Oil Storage) (England) Regulations. Further guidance may be obtained from the local environmental agency office.
Recommended Materials	: For containers or container linings, use mild steel or high
Unsuitable Materials	density polyethylene. : PVC.
Additional Information	 Polyethylene containers should not be exposed to high temperatures because of possible risk of distortion.

Print Date 03.11.2011

3/9

Exposure to this product should be reduced as low as reasonably practicable. Reference should be made to the Health and Safety Executive's publication "COSHH Essentials".

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

If the American Conference of Governmental Industrial Hygienists (ACGIH) value is provided on this document, it is provided for information only.

Occupational Exposure Limits

Material	Source	Туре	ppm	mg/m3	Notation		
Oil mist, mineral	ACGIH	TWA [Inhalable fraction.]		5 mg/m3			
Exposure Contro Personal Protect Equipment Respiratory P	ive :	depending upo based on a risi Appropriate me airborne conce mist formed, th concentrations Personal prote recommended No respiratory conditions of u practices, prec material. If eng concentrations health, select r	The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include: Adequate ventilation to control airborne concentrations. Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated. Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers. No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material. If engineering controls do not maintain airborne concentrations to a level which is adequate to protect worker health, select respiratory protection equipment suitable for the specific conditions of use and meeting relevant legislation.				
Hand Protecti	ion :	air-filtering res combination of combined part >65 °C (149 °F Where hand co gloves approve US: F739) mad suitable chemi gloves. Suitable	pirators are mask and f iculate/orgar []] meeting E ontact with the d to relevar de from the f cal protectio lity and dura	suitable, select ar ilter. Select a filter nic gases and vap	s suitable for pours [boiling point ccur the use of Europe: EN374, s may provide or nitrile rubber dependent on		

Print Date 03.11.2011

MSDS_GB

Eye Protection Protective Clothing	 resistance of glove material, glove thickness, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended. Wear safety glasses or full face shield if splashes are likely to occur. Approved to EU Standard EN166. Skin protection not ordinarily required beyond standard issue work clothes.
Monitoring Methods	: Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. For some substances biological monitoring may also be appropriate.
Environmental Exposure Controls	: Minimise release to the environment. An environmental assessment must be made to ensure compliance with local environmental legislation.
9. PHYSICAL AND CHEMICAL	PROPERTIES
Appearance Odour pH Initial Boiling Point and Boiling Range Pour point	 Brown. Liquid at room temperature. Slight hydrocarbon. Not applicable. > 280 °C / 536 °F estimated value(s) Typical -51 °C / -60 °F
Flash point Upper / lower Flammability or Explosion limits Auto-ignition temperature Vapour pressure	 Typical 210 °C / 410 °F (COC) Typical 1 - 10 %(V) (based on mineral oil) > 320 °C / 608 °F < 0.5 Pa at 20 °C / 68 °F (estimated value(s))
Density Water solubility	 Typical 840 kg/m3 at 15 °C / 59 °F Negligible.

n-octanol/water partition : > 6 (based on information on similar products)

coefficient (log Pow)	, , , , , , , , , , , , , , , , , , ,	
Kinematic viscosity	: Typical 26.8 mm2/s at 40 °C / 104 °F	-
Vapour density (air=1)	: > 1 (estimated value(s))	

Vapour density (air=1): > 1 (estimated value)Evaporation rate (nBuAc=1): Data not available

10. STABILITY AND REACTIVITY

Stability: Stable.Conditions to Avoid: Extremes of temperature and direct sunlight.

Print Date 03.11.2011

5/9

Materials to Avoid Hazardous Decomposition Products	:	Strong oxidising agents. Hazardous decomposition products are not expected to form during normal storage.
11. TOXICOLOGICAL INFORM	ATI	ON
Basis for Assessment	:	Information given is based on data on the components and the toxicology of similar products.
Acute Oral Toxicity Acute Dermal Toxicity Acute Inhalation Toxicity	:	Expected to be of low toxicity: LD50 > 5000 mg/kg , Rat Expected to be of low toxicity: LD50 > 5000 mg/kg , Rabbit Not considered to be an inhalation hazard under normal conditions of use.
Skin Irritation	:	Expected to be slightly irritating. Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.
Eye Irritation	:	Expected to be slightly irritating.
Respiratory Irritation	:	Inhalation of vapours or mists may cause irritation.
Sensitisation	:	Not expected to be a skin sensitiser.
Repeated Dose Toxicity	:	Not expected to be a hazard.
Mutagenicity	:	Not considered a mutagenic hazard.
Carcinogenicity	:	Product contains mineral oils of types shown to be non- carcinogenic in animal skin-painting studies. Highly refined mineral oils are not classified as carcinogenic by the International Agency for Research on Cancer (IARC). Other components are not known to be associated with carcinogenic effects.
Reproductive and Developmental Toxicity Additional Information	:	Not expected to be a hazard. Used oils may contain harmful impurities that have accumulated during use. The concentration of such impurities will depend on use and they may present risks to health and the environment on disposal. ALL used oil should be handled with caution and skin contact avoided as far as possible.

12. ECOLOGICAL INFORMATION

Ecotoxicological data have not been determined specifically for this product. Information given is based on a knowledge of the components and the ecotoxicology of similar products.

Acute Toxicity : Poorly soluble mixture. May cause physical fouling of aquatic organisms. Expected to be practically non toxic: LL/EL/IL50 > 100 mg/l (to aquatic organisms) (LL/EL50 expressed as the nominal amount of product required to prepare aqueous test extract). Mineral oil is not expected to cause any chronic

Print Date 03.11.2011

Mobility Persistence/degradability	:	effects to aquatic organisms at concentrations less than 1 mg/l. Liquid under most environmental conditions. Floats on water. If it enters soil, it will adsorb to soil particles and will not be mobile. Expected to be not readily biodegradable. Major constituents are expected to be inherently biodegradable, but the product
Bioaccumulation	:	contains components that may persist in the environment. Contains components with the potential to bioaccumulate.
Other Adverse Effects	:	Product is a mixture of non-volatile components, which are not expected to be released to air in any significant quantities. Not expected to have ozone depletion potential, photochemical ozone creation potential or global warming potential.
13. DISPOSAL CONSIDERATIO	NS	
Material Disposal	:	Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses.
Container Disposal	:	Dispose in accordance with prevailing regulations, preferably to a recognised collector or contractor. The competence of the collector or contractor should be established beforehand.
Local Legislation	:	Disposal should be in accordance with applicable regional, national, and local laws and regulations. EU Waste Disposal Code (EWC): 13 02 05 mineral-based non- chlorinated engine, gear and lubricating oils. Classification of waste is always the responsibility of the end user.

14. TRANSPORT INFORMATION

ADR

This material is not classified as dangerous under ADR regulations.

RID

This material is not classified as dangerous under RID regulations.

ADN

This material is not classified as dangerous under ADNR regulations.

IMDG

This material is not classified as dangerous under IMDG regulations.

IATA (Country variations may apply)

This material is either not classified as dangerous under IATA regulations or needs to follow country specific requirements.

15. REGULATORY INFORMATION

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

EC Classification EC Symbols EC Risk Phrases EC Safety Phrases Chemical Inventory Status	::	Not classified as dangerous under EC criteria. No Hazard Symbol required Not classified. Not classified.
EINECS	:	All components listed or polymer exempt.
TSCA	:	All components listed.
Sensitiser not sufficient to classify	:	Contains calcium sulphonate. Contains ethoxylated amine. May produce an allergic reaction.
Other Information	:	Environmental Protection Act 1990 (as amended). Health and Safety at Work Act 1974. Consumers Protection Act 1987. Control of Pollution Act 1974. Environmental Act 1995. Factories Act 1961. Carriage of Dangerous Goods by Road and Rail (Classification, Packaging and Labelling) Regulations. Chemicals (Hazard Information and Packaging for Supply) Regulations 2002. Control of Substances Hazardous to Health Regulations 1994 (as amended). Road Traffic (Carriage of Dangerous Substances in Packages) Regulations. Merchant Shipping (Dangerous Goods and Marine Pollutants) Regulations. Road Traffic (Carriage of Dangerous Substances in Road Tankers in Tank Containers) Regulations. Road Traffic (Training of Drivers of Vehicles Carrying Dangerous Goods) Regulations. Reporting of Injuries, Diseases and Dangerous Occurrences Regulations. Health and Safety (First Aid) Regulations 1981. Personal Protective Equipment (EC

Print Date 03.11.2011

8/9

Directive) Regulations 1992. Personal Protective Equipment at Work Regulations 1992.

16. OTHER INFORMATION

R-phrase(s)

R22 R34 R43 R50	Not classified. Harmful if swallowed. Causes burns. May cause sensitisation by skin contact. Very toxic to aquatic organisms.		
MSDS Version	Number	:	2.0
MSDS Effective	e Date	:	02.11.2011
MSDS Revision	ns	:	A vertical bar () in the left margin indicates an amendment from the previous version.
MSDS Regulat MSDS Distribu			Regulation 1907/2006/EC The information in this document should be made available to all who may handle the product.
Disclaimer		:	This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.