

Maintenance

TECHNICAL SPECIFICATIONS

Lubricants and fluids

Part	Variant	Specification
Engine oil	All vehicles	SAE 5W-30 meeting Jaguar specification WSS M2C913-B.
Power steering fluid	All vehicles	DEXRON III
Brake fluid	All vehicles	Shell DOT4 ESL. If Shell DOT4 ESL is not available seek advice from your Jaguar Dealer.
Windshield washer	All vehicles	Windshield wash with frost protection
Coolant	All vehicles	50% mixture of antifreeze to specification WSS M97B44 (coloured orange) Extended Life Coolant and water.

Capacities

Item	Variant	Capacity
Fuel tank	All vehicles	71.1 litres (18.8 gallons)
Fill capacity (when the fuel gauge indicates empty)	All vehicles	65.1 litres (17.2 gallons)
Reserve capacity (when the fuel gauge indicates empty)	All vehicles	6.0 litres (1.6 gallons)
Engine oil refill and filter change	All vehicles	7.0 litres (14.8 pints)
Windshield and headlamp washer reservoir	4.2 normally aspirated engine	6.3 litres (13.3 pints)
	4.2 litre supercharged engine	6.6 litres (14.0 pints)
Cooling system, including reservoir and climate control	4.2 litre normally aspirated engine	10.4 litres (22.0 pints)
	4.2 litre supercharged engine	10.0 litres (21.1 pints)

Note: The quoted capacities are approximate and provided as a guide only. All oil levels must be checked using the dipstick or level plugs as applicable.

Note: Avoid the risk of running out of fuel and never intentionally drive the vehicle when the fuel gauge indicates that the tank is empty. When refuelling after the fuel gauge reads empty, you may not be able to add the fuel quantity shown above as there will be a small reserve remaining in the tank.